

**PRODUCT SELECTOR GUIDE – Aeration Basins, Clarifiers,  
Floculators, Screening, and Settling Tanks**

**INTERNAL APPLICATIONS**

Concrete - Internal	Flexcel II TX	60 mils/1500 microns or more
Steel - Submerged	Corrocote II WasteLiner	20 mils/500 microns

**EXTERNAL APPLICATIONS**

Concrete - External Aboveground	AcrylaThane Tufsheen	12 mils/300 microns or more 12 mils/300 microns or more
Concrete - External Belowground	Corrocote II Classic	40 mils/1000 microns or more
Steel - Atmospheric	AcrylaThane Tufsheen	7 mils/175 microns 10 mils/250 microns

**REPAIRS**

Corrocote II WasteLiner	TX Touch Up, TX-II Touch Up GP II Touch Up, GP II (E) Touch Up	As required
Flexcel	Flexcel II, TX Touch Up	As required
Corrocote II Classic	TX Touch Up, TX II Touch Up, GP II Touch Up, GP II (E) Touch Up	As required
AcrylaThane	Aliphatic Touch Up	As required
Tufsheen	Aliphatic Touch Up	As required



**For specific application recommendation contact Madison Chemical.  
Phone (905) 878-8863 Fax (905) 878-1449 e-mail [sales@madisonchemical.com](mailto:sales@madisonchemical.com)**