



PRODUCT SELECTOR GUIDE – Ductile Iron Pipe

INTERNAL APPLICATIONS

Standard Sewage, Wastewater, Reclaimed Water Temperature less than 60°C (140°F)	Corropipe II WasteLiner (AM/CM versions available)	40 mils (1000 microns)
Standard Sewage, Wastewater, Reclaimed Water Temperature less than 90°C (195°F)	Corropipe II UltraLiner (AM/CM versions available)	40 mils (1000 microns)
Potable Water, Foodstuffs Temperature less than 60°C (140°F)	Corropipe II PW	40 mils (1000 microns)
Fuels, Chemicals, Seawater (see Madison for limits) Temperature less than 90°C (195°F)	Corropipe II UltraLiner (AM/CM versions available)	40 mils (1000 microns)
Severe Abrasion	Corropipe II Abrasion	Contact Madison
Sea Water Temperature less than 65°C (150°F)	Corropipe II UltraLiner (AM/CM versions available)	40 mils (1000 microns)

EXTERNAL APPLICATIONS

Buried Corrosion Protection Temperature less than 90°C (195°F)	Corropipe II TX-15 Corropipe Slow Set	25 mils (625 microns)
Buried Corrosion Protection Temperature less than 125°C (250°F) Dry	Corroclad 2000 HT	25 mils (625 microns)
Severe Abrasion	Corropipe II TX-15 Corroclad 2000 Corroclad 2000HT (CM) version available	40 to 80 mils (1000 to 2000 microns)
Above Ground Corrosion Protection	Corropipe II Omni with Acrylathane Topcoat	12 mils (300 microns) 5 mils (125 microns)

FIELD JOINTS AND TOUCH UP

Corropipe II WasteLiner Corropipe II TX-15 Corropipe II TX-45 Corropipe II UltraLiner Corropipe II Slow Corroclad 2000 Corroclad 2000HT	Parent Coating Corropipe "S" GP II Touch Up GP II (E) Touch Up	25 mils (625 microns)
For Corropipe II PW	PW Touch Up GP II Touch Up	25 mils (625 microns)
For Corropipe II Abrasion	Flexcel Mastic Flexcel II Touch Up	25 mils (625 microns)

