



PRODUCT SELECTOR GUIDE - Pipe Coatings and Linings

INTERNAL APPLICATIONS

Standard Sewage, Wastewater, Reclaimed Water Temperature less than 60°C (140°F)	Corropipe II WasteLiner (AM/CM versions available)	20 mils (500 microns)
Standard Sewage, Wastewater, Reclaimed Water Temperature less than 90°C (195°F)	Corropipe II UltraLiner	20 mils (500 microns)
Potable Water, Foodstuffs Temperature less than 60°C (140°F)	Corropipe II PW	20 mils (500 microns)
Fuels, Chemicals, Seawater (see Madison for limits) Temperature less than 90°C (190°F)	Corropipe II UltraLiner	20 mils (500 microns)
Severe Abrasion	Corropipe II Abrasion Corropipe II WasteLiner (CM) Corropipe II UltraLiner (CM)	Contact Madison

EXTERNAL APPLICATIONS

Buried Corrosion Protection Temperature less than 90°C (190°F)	Corropipe II TX-15 Corropipe II Slow Set	20 mils (500 microns)
Buried Corrosion Protection Temperature less than 125°C (250°F) Dry	Corroclad 2000 HT	20 mils (500 microns)
Rock Shield, Slip Bore, River Crossing Direct Jack	Corropipe II TX-15 (CM) versions available CorroClad 2000-05-25 CorroClad 2000 HT	40 to 80 mils (1000 to 2000 microns)
Above Ground Corrosion Protection	Corropipe II Omni with AcrylaThane Top Coat	20 mils (500 microns) 5 mils (125 microns)

FIELD JOINTS AND TOUCH-UP

for Corropipe II WasteLiner	Parent Coating GP II (E) Touch Up	20 mils (500 microns)
for Corropipe II PW	PW Touch Up	20 mils (500 microns)
for Corroclad 2000	Corropipe 'S' GP II (E) Touch Up	20 mils (500 microns)



**For specific application recommendation contact Madison Chemical.
Phone (905) 878-8863 Fax (905) 878-1449 e-mail sales@madisonchemical.com**